



More than Fingerprint!

IDLink Netfinger 5000 FACE is a multi-modal biometric solution enable with Fingerprint, Face Recognition and RFID and Key-in authentication that comes with accurate and rapid matching speed for stable Time Attendance and Door Access control.


IDLink Netfinger 5000 Face is designed to be performed on the 5.7 inches TFT touch screen which is convenient to display the important notice and OEM logo, TCP/IP and optional WiFi and USB. It offers you enterprise level of Entry and Time Attendance management with its LAN communication-based network infrastructure, enabling integrated monitoring and systematic management of multiple terminals operated independently on a remote location and SDK to be easily integrated with customer's application.

INNOVATIVE NETFINGER 5000 FACE

- **Multimodal Biometric**
- **Large Scale System**
- **Wireless LAN**

INNOVATIVE NETFINGER 5000 FACE

Features



- **5.7 inch true Color LCD with Touch Screen**
 - Large LCD enable for company logo, important notice.
 - **Fingerprint and Face quality display in the initial stage of authentication process**
 - User Friendly Interface
- **Auto-on function with Live Finger Detection**
- **Wireless LAN (optional)**
 - Easy to install in anywhere
- **USB Memory Slot**
 - User Information & Log data Up/Download
 - Firmware Upgrade
- **Built-in Camera (optional)**
 - Live picture taken whenever log event occurs
- **Large Scale System**
 - Max 2,000 terminals connected in one network
- **Face Technology**
 - Face Detection
 - Face Recognition
 - Multi-modal enhanced security



Description	Specifications
CPU	32bit / 620MHz
Memory	256MB Flash / 256DRAM
Display	5.7 inch VGA Colour / Touch-screen
1:N fingerprint Identification Time	Less than 1 sec (4,000 templates)
Template Capacity	Normal : fingerprint 100,000 templates (2 templates / 1 finger) Face Face : fingerprint 40,000 templates, face 3,000 user
Log Capacity	100,000 logs
Communication	TCP / IP, Wiegand (26/34 bits)
Lock	Deadbolt, EM Lock, Door Strike, Automatic Door
USB Memory Slot	Supports
Camera	Embedded
Fake / Latent Fingerprint Recognition	Available
Size	167 x 146 x 52 (W x H x D)
Environment	-20~60 °C
Certificate	KC, CE, FCC



DISTRIBUTOR / RESELLER