



IR DOME CAMERA

- Compact Design & DIS
- Advanced Engineering Design, High Reliability
- ICR & weather-proof
- IR cut filter with auto switch
- Min. illumination: 0.1 Lux @F1.2 (0 Lux with IR)
- Smart IR mode
- Auto white balance, auto gain control, electronic shutter control and backlight
- Ingress Protection : IP66

Description	Specifications
Camera	
Image Sensor	1/3" DIS
Signal System	PAL/NTSC
Effective Pixels	976(H) x 496(V)
Min. Illumination	0.1 Lux @ (F1.2AGC ON), 0 Lux with IR
Shutter Speed	PAL: 1/50 s to 1/100,000 s NTSC: 1/60 s to 1/100,000 s
Lens	3.6mm (2.8mm, 6mm optional) ; Angle of View: 68.4° (3.6mm)
Lens Mount	M12
Day & Night	IR cut filter with auto switch
Horizontal Resolution	700TVL
Synchronization	Internal synchronization
HD Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62dB
General	
Working Temp / Humidity	-40°C ~ 60°C (-40°F ~ 140°F) / Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10%
Power Consumption	Max. 1.8 W (Max. 4 W with IR cut filter on)
Weather Proof Ratings	IP66
IR Range	Approx. 10 to 20 meters
Dimensions	Φ89.5 × 69.8 mm (Φ3.52" × 2.75")
Weight	260 g (0.57 lbs)