



Description	Specifications
Camera	
Image Sensor	1MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	1296(H)*732(V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1 / 25 (1 / 30) s to 1 / 50,000s
Lens	2.8mm, 3.6mm, 6mm optional Angle of View: 70.9° (3.6mm), 92° (2.8mm), 56.7° (6mm)
Lens Mount	M12
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	720p@25fps / 720p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	More than 62dB
General	
Working Temp / Humidity	-40°C ~ 60°C (-40°F ~ 140°F) / Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 4W
Weather Proof Ratings	IP66
IR Range	Up to 20m
Dimensions	Φ89.5 × 69.8 mm(Φ3.52" × 2.75")
Weight	280g

FULL HD720P TURRET CAMERA

- 1 Megapixel high-performance CMOS
- Analog HD output, up to 720P resolution
- True Day / Night
- DNR, Smart IR
- Up to 20m IR distance
- IP66 weatherproof

