



Description	Specifications
<b>Camera</b>	
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2AGC ON), 0 Lux with IR
Shutter Time	1 / 25 (1 / 30) s to 1 / 50,000s
Lens	2.8mm, 3.6mm, 6mm optional
	Angle of View: 103°(2.8mm), 82.2°(3.6mm), 54°(6mm)
Lens Mount / Day & Night	M12
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps / 1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	More than 62dB
<b>General</b>	
Operating Conditions	-40°C ~ 60°C ( -40°F ~ 140°F) / Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 4W
Protection Level	IP66
IR Range	Up to 20m
Dimensions	φ89.5 x 69.8mm (φ3.52" × 2.75")
Weight	280g

# FULL HD1080P BULLET CAMERA

- 2 Megapixel high-performance CMOS
- Analog HD output, up to 1080P resolution
- True Day / Night, Smart IR
- Up to 20m IR distance
- IP66 weatherproof

