



Description	Specifications
Camera	
Image Sensor	1/3" DIS
Signal System	PAL/NTSC
Effective Pixels	976(H) x 496(V)
Min. Illumination	0.1 Lux @ (F1.2AGC ON), 0 Lux with IR
Shutter Speed	PAL: 1/50 s to 1/100,000 s ⁻¹ ; NTSC: 1/60 s to 1/100,000 s
Lens	3.6mm (2.8mm, 6mm optional); Angle of View: 68.4° (3.6mm)
Lens Mount	M12
Day & Night	IR cut filter with auto switch
Horizontal Resolution	700TVL
Synchronization	Internal synchronization
HD Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62dB
General	
Working Temp / Humidity	-40°C ~ 60°C (-40°F ~ 140°F) / Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 1.8 W (Max. 4 W with IR cut filter on)
Weather Proof Ratings	IP66
IR Range	20m
Dimensions	φ70×149.5 mm (φ2.76" ×5.89")
Weight	360g (0.79lbs)

IR BULLET CAMERA

- 700 TVL Horizontal Resolution
- True Day/Night
- 2.8 / 3.6 / 6mm Fixed Lens, 0.1 lux / F1.2
- 20m IR Distance
- Wide Operating Temperature Range: -40°C to 60°C(-40°F to +140°F)

