



EMBEDDED NETWORK VIDEO RECORDER

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 16/32-ch network cameras can be connected with 100M/200M incoming bandwidth
- 4 SATA interfaces
- Plug & Play with 16 independent PoE network interfaces
- Support network detection, including network delay, packet loss, etc

EMBEDDED NETWORK VIDEO RECORDER

Description	Specifications	
	NVR-7716NI-4 NVR-7716NI-4/16P	NVR-7732NI-4 NVR-7732NI-4/16P
Video / Audio Input		
IP Video Input	16-ch	32-ch
Two-Way Audio Input	1-ch, RCA (2.0 Vp-p, 1kΩ)	
Network		
Incoming Bandwidth	100Mbps	200Mbps
Outgoing Bandwidth	80Mbps	
Remote Connection	128	
Video / Audio Output		
Recording Resolution	5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Frame Rate	Main Stream : 50 fps (P) / 60 fps (N) Sub Stream : 50fps (P) / 60fps (N)	
HDMI / VGA Output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz	
Audio Output	1-ch, RCA (Linear, 1kΩ)	
Decoding		
Live View / Playback resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Capability	6-ch@4CIF, 12-ch@720P, 6-ch@1080P	
Hard disk		
SATA	4 SATA interfaces for 2 HDDs + 1 DVD-R/W (default), or 4HDDs	
eSATA (Optional)	1 eSATA interface	
Capacity	Up to 4TB capacity for each HDD	
External Interface		
Network Interface	2 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interfaces	
Serial Interface	RS-232 and RS-485	
USB Interface	2 × USB 2.0 + 1 × USB 3.0	
Alarm In/Out (Optional)	16 / 4 (optionally can be expanded to 16 / 8)	
Others		
Power Supply	100 to 240 VAC	
Consumption (Without hard disk)	≤20W	
Working Temperature	-10 °C to +55 °C (+14 °F to + 131 °F)	
Working Humidity	10 % to 90 %	
Chassis	19-inch rack-mounted 1.5U chassis	
Dimension (W x D x H)	445 × 390 × 70 mm (17.5"× 15.3" × 2.8")	
Weight (Without hard disk)	≤ 4 Kg (8.82 lb)	