



iDlink
systems

www.idlinksystems.com

ROBUST NETFINGER T3



Fingerprint, RF card, Password



2.4" TFT Color LCD



USB Memory Slot for Data Transfer



User-Defined Functions(F1-F4)



Dust and Water Proof



Superior Matching Engine



Touch Keypad



Identification of Superior Quality

- **Compact and Stylish**
- **Cost Effective**
- **Friendly Interface**
- **Multifactor Authentication**

IDLink Netfinger T3 is an innovative biometric fingerprint reader for time and attendance application. It has multifactor authentication such as fingerprint, RF card and password.

It features the fastest commercial-based fingerprint matching algorithm and high-performance, high-image quality optical fingerprint sensor. The 2.4" TFT can display more information vividly, including fingerprint image quality and verification result etc. TCP / IP communication is standard and make sure the data transmission between terminal and PC can be easily done within several seconds.

IDLink Netfinger T3 is highly competitive and feature rich. Compact and stylish design with a user-friendly user interface, IDLink Netfinger T3 also come with USB memory slot and has superior matching engine.



Features

- ▶ IP54 : Dustproof & Waterproof
- ▶ 2.4" TFT Color LCD
- ▶ Touch Keypad
- ▶ USB Memory Slot : Easy data transfer using USB memory stick
- ▶ Superior Matching Engine : 1st rank in FVC (Fingerprint Verification Competition)
- ▶ Function Key : User-defined functions & Clock in / Clock out / Absence / Return
- ▶ Multifactor Authentication : Fingerprint, RF card, Password

Product Specifications

Description	Specifications
CPU	S3C6410 (ARM11 667MHz)
Memory	256MB DRAM / 256MB Flash
Display	2.4" TFT Color LCD
Sensor	Optical / 500 DPI
Authentication Type	Fingerprint, Password, RF card
1:1 Time	< 0.2 sec.
1:N Time	< 1 sec.(4,000 templates)
Template Capacity	20,000 templates (2 templates / 1 finger, 10,000 users)
Log Capacity	100,000 logs
Communication	TCP / IP, Wiegand (26/34 bits)
Lock	Deadbolt, EM Lock, Door Strike, Automatic Door
Environment	-20~60 °C / < RH 90%
Certificate	KC, CE, FCC
Dimensions	75(W) x 182.5(H) x 39.2(D) mm