

UBIO-X PRO 2 - FACE & FINGERPRINT RECOGNITION TERMINAL



- Liveness Detection
- Anti-Spoofing Attacks Against Photos, Video & 3D Masks.
- High Ambient Light Conditions
- Visible Light Technology
- Patented Fake Fingerprint Detection
- Face Recognition at a Distance up to 3m
- High Speed Face and Fingerprint Matching
- Easy Face Enrollment - Use Camera or Phone Picture



Liveness Detection
Anti-Spoofing attacks against photos, videos & 3D masks.



Face Recognition at a Distance
up to 3M



High Ambient light conditions
Illuminance up to 25,000 Lux



High Speed Face and Fingerprint Matching



Visible Light Technology
with IR Technology



Easy Face Enrollment-Use Camera or Phone Picture



Patented Fake Fingerprint Detection

UBio-X Pro 2 is multi-biometric identification Time Attendance and Access control, integrated with high speed processor. It provide liveness detection, anti-spoofing attacks against photo, video and 3D masks. It also provide easy face enrollment using camera or phone picture.

Come with high ambient light conditions, it can achieve up to 25,000 lx of operating illuminance which in turn, brings all-round confidence regardless of lighting conditions. The device is able to detect face up to a 3M distance. and has a high speed face and fingerprint matching.

Features



- ▶ **Liveness Detection**
- ▶ **Anti-Spoofing attacks against photos, videos & 3D masks**
- ▶ **Face Recognition of a distance up to 3m**
- ▶ **High Speed Matching Algorithm**
- ▶ **The System can work in different light condition even in the dark**
- ▶ **Visible Light Technology with IR Technology**
- ▶ **Operating Illuminance of up to 30,000 Lux**
- ▶ **Easy Face Enrollment - Use Camera or Phone Picture**

Product Specifications

Description	Specifications
Operating System	Android 6.0
User Capacity	Up to 20,000 (1 Face / 1 User) Up to 500,000 (1 Finger / 1 User) Fingerprint 1: 200,000 Templates < 1sec Face 1: 20,000 Templates < 1 sec Event Logs : 10,000,000 Photo Logs : 20,000
Fingerprint Sensor Type	Optical Sensor
CPU	1.0 GHz Quad Core (Cortex-A9) + 900MHz Dual Core (Cortex-A7)
Memory	eMMC 16GByte + 8 GByte DDR3 2GB RAM (512MB x 4) +512MB
Display	5" Colour TFT LCD with Touch
RF / Smartcard Option	13.56 MHz Smart Card Reader 125KHz – EM, HID Prox / Class(Optional) RF Card Reader
Interface	RS-232 / RS-485 Wiegand IN / OUT WiFi (Optional) SD Card Socket
Operating Temperature	-20 ~ 60°C
Dimension	149.7 x 208 x 56.4mm (W x H x D)
Certification	KC, CE, FCC